

Continual Learning for Vision

Manling Li
Northwestern University
Amazon Scholar
manling.li@northwestern.edu



NORTHWESTERN
UNIVERSITY



MLL LAB
Machine Learning and Language

How Models Learn (and Fail to Learn) the Physical World



*A robot arm is placing
the banana on top of
the coaster*



What we expect



banana → monkey → jump

Output from Wan2.2

World Models


what we want

**?
==**


Surface Behavior

what we truly learn


GPT-6



HumanClaw




Co-Evolving: Let's train them!



**World models are not about surface behavior,
but the reasoning that matters to the downstream agents**

The Age of Agents

Capability








What's Left for Humans?

What is the missing intelligence: Abstraction



RSI: Recursive Self-Improvement?

Abstraction as Compression

Model vs Human:

Data



Abstraction



Model




1 Million Molecules



Statistical
Correlation



Human



10 Molecules



Chemical Law
(Abstraction)

On the measure of intelligence

*The intelligence of a system is a measure of its **skill-acquisition** efficiency over a scope of **tasks**, with respect to **priors**, **experience**, and **generalization difficulty**.*

— Collet, et al. On the measure of intelligence, 2019.


Why is RAG not enough?

DeepResearch




AutoResearch

Why is RAG not enough?




Now: Recursive Self Improvement (RSI)



Recursive Self Improvement: AutoResearch

Step 4: The optimal code feeds back into the next generation.





The Path to Recursive Self-Improvement

The definition of Recursive Self-Improvement




Irving John Good (1965)


The definition of Recursive Self-Improvement




Agent = Model + Harness




Agent = Model + Harness



Layer 1: Artifact Self-Improvement




Layer 1: Artifact Self-Improvement




Layer 2: Harness Self-Improvement

Now make the operating system around the model editable




Layer 3: Model Self-Improvement


Finally move the write-back path inside the model



Experience is compiled into persistent model parameters.



RAGEN-2: Why reasoning collapse in long-horizon?



$$H(Z) = H(Z|X) + I(X; Z)$$

X : Input
 Z : Reasoning

PRIORS

Common
Knowledge

Instruction
Following

World
Modeling

Reasoning
Planning

Human
Experience

STAGES

Pre-training

Self-Supervised
Finetuning

Mid-training

Reinforcement
Learning

Harness

DATA

Static Internet Data:
Books, Images, Videos...

Human Annotations:
<instructions, answers>

Play Data:
Env, Tools, External Data

Task Feedback:
Verifiers (Goal Definitions)

Prompt Engineering
→ Context Engineering
→ Harness Engineering
→ Graph Engineering

Brute-force Scaling



Continual Learning

(We are here now)



Human + World

(Our future)

PRIORS

Common
Knowledge

Instruction
Following

World
Modeling

Reasoning
Planning

Human
Experience

STAGES

Pre-training

Self-Supervised
Finetuning

Mid-training

Reinforcement
Learning

Harness

DATA

Static Internet Data:
Books, Images, Videos...

Human Annotations:
<instructions, answers>

Play Data:
Env, Tools, External Data

Task Feedback:
Verifiers (Goal Definitions)

Prompt Engineering
→ **Context Engineering**
→ **Harness Engineering**
→ **Graph Engineering**

Brute-force Scaling



Continual Learning

(We are here now)



Human + World

(Our future)

world model reasoning through RL

1. *What are failure modes of RL?*

→ *Exploration vs Exploitation*

2. *What priors should we encourage for exploration?*

→ *World Model*

3. *When is the best stage to encourage it?*

→ *Mid-training vs RL*


Planning with the Views

Kangrui Wang, Linjie Li, Zhengyuan Yang, Shiqi Chen, Zihan Wang

Li Fei-Fei, Jiajun Wu, Leonidas Guibas, Lijuan Wang, Manling Li



Initial view



Top-down View



Target view

Planning with the Views

Environment. Top: point-cloud scene **top-down** view with two viewpoints (**initial** in **blue**, **target** in **orange**). Bottom: rendered first-person views from each viewpoint.



Rendered Initial View




Rendered Target View

Path-to-View. Given **top-down**, **initial** view and the action sequence: [turn_right x2, ...], which is the correct **target** view?



View-to-Path. Given **top-down**, **initial** and the **target** view, which is the correct action sequence?




A: turn_left, ...

B: turn_right, ...

C: look_up, ...

D: move_left, ...

Interactive View Planning. Given **top-down**, **initial** and the **target** view, please find the correct viewpoint of the target view.




Model	Path-to-View (P2V)			View-to-Path (V2P)			View Planning (IVP)			Overall
	Short	Long	All	Short	Long	All	Short	Long	All	
Random Response	20.7	24.6	23.3	24.3	26.5	25.7	2.2	0.0	0.8	16.6
<i>Proprietary Models</i>										
GPT-5.4 Pro	70.7	43.8	53.1	72.4	39.0	50.7	32.6	11.0	18.5	40.8
Gemini 3.1 Pro	63.6	40.9	48.8	53.0	47.7	49.5	28.8	17.4	21.4	39.9
GPT-5.4	57.1	42.9	47.8	60.5	37.5	45.6	33.7	7.5	16.6	36.7
Grok 4.20 Beta	61.4	38.0	46.1	44.9	44.5	44.6	17.4	2.9	7.9	32.9
GPT-5.1	60.3	35.1	43.9	52.4	33.4	40.1	12.0	3.2	6.2	30.1
Claude Opus 4.6	46.7	28.4	34.8	47.6	38.4	41.6	23.9	3.8	10.8	29.0
Gemini 3 Pro	50.5	31.0	37.8	44.9	35.5	38.8	13.6	7.0	9.3	28.6
<i>Open-Weight Models</i>										
Qwen3.5-397B	57.6	30.1	39.7	44.3	30.8	35.5	12.5	0.0	4.3	26.5
GLM-4.6V	36.4	23.2	27.8	31.4	29.7	30.2	9.2	1.2	4.0	20.7
Qwen2.5-VL-72B	28.3	29.3	28.9	35.7	29.9	31.9	2.2	0.6	1.1	20.7
Qwen3-VL-32B	27.2	27.5	27.4	41.1	28.5	32.9	4.3	0.0	1.5	20.6
Kimi K2.5	35.9	24.6	28.5	18.4	29.4	25.5	4.9	1.2	2.5	18.8
Qwen2.5-VL-7B	23.9	32.5	29.5	27.0	22.7	24.2	7.1	0.0	2.5	18.7

View Transition like a View World Model



view A

turn left | move forward





view B

Even inside a rollout that missed its goal, going $A \rightarrow B$ is a view transition that can serve as valid supervision.



Continual Learning with a View World Model?

Step 1 • View Graph via On-Policy Exploration





The agent explores **ViewSuite** scenes from its own experience.

Step 1 • View Graph via On-Policy Exploration





Rollout 1 wanders the scene – and misses.

Step 1 • View Graph via On-Policy Exploration




Rollout 2 also fails – but it crosses rollout 1.

Step 1 • View Graph via On-Policy Exploration




Every rollout misses the target. Yet together they trace the whole scene.

Step 2 • A View Graph Emerges



Shared viewpoints **merge**: nodes are views, edges are actions.

Step 2 • A Path Emerges



A path the agent **never walked** now connects initial → target.

Step 3 • Reformulate into a Demo

initial view

target view



input: initial + target view output: the action sequence


Any sampled path becomes a demo
valid even though no rollout reached the target.

View Planning via Self-Exploration

RL Exploration



PPO with Interactive View
Planning Reward




View Planning via Self-Exploration


RL Exploration



PPO with Interactive View Planning Reward



On-Policy View Graph Construction




View Planning via Self-Exploration


RL Exploration



PPO with Interactive View Planning Reward




On-Policy View Graph Construction



→ Actions (e.g turn_left | move_forward)


View Graph Distillation

Path Sampling: length=5



Start Node: Initial View
End Node: Target View
Intermediate Node: Turn-by-turn observations

Reformulated Training Example




Action 1
turn_right | look_up

Action 2
move_backward

Action N-1
move_left | turn_right

Action N
answer(...)




View Planning via Self-Exploration


RL Exploration



PPO with Interactive View Planning Reward




On-Policy View Graph Construction



View Graph Distillation

Path Sampling: length=5



Start Node: Initial View
End Node: Target View
Intermediate Node: Turn-by-turn observations

Reformulated Training Example



SFT Training



Interactive View Planning



View Difference

Cross-entropy loss on reformulated data




View Planning via Self-Exploration


RL Exploration



PPO with Interactive View Planning Reward




On-Policy View Graph Construction



View Graph Distillation

Path Sampling: length=5



Start Node: Initial View
End Node: Target View
Intermediate Node: Turn-by-turn observations

Reformulated Training Example



SFT Training

Interactive View Planning
View Difference

Cross-entropy loss on reformulated data



Next Iteration

From **2.5%** to **47.8%**

Qwen2.5-VL-7B (base)

2.5%

GPT-5.4 Pro

18.5%

Gemini 3.1 Pro

21.4%

Ours

47.8%

[View Planning \(arxiv 2026\)](#)

From 2.5% to 47.8%

Qwen2.5-VL-7B (base)

2.5%

GPT-5.4 Pro

18.5%

Gemini 3.1 Pro

21.4%

Ours

47.8%

A 7B model trained only on its own exploration **beats every frontier VLM.**

[View Planning \(arxiv 2026\)](#)


Another Direction: Latency-Aware Planning, Budget-Aware Planning




Real-time latency creates
a performance gap




Our method recovers most
of the zero-latency performance






ODE-Steering

Modeling a as ODE




ODE-Steering: Control Barrier Function

If we can draw a **safe boundary** for a




ODE-Steering: Control Barrier Function

If we can draw a **safe boundary** for a



ODE-Steering: Control Barrier Function


How to learn the **safe boundary** h ?



Steering Vector $v(a) = \nabla h(a)$


Difference-in-Means [1]

$$\mu_+ - \mu_-$$




Linear Probe [2]

$$\theta$$



$$\nabla h(a) = J_{\phi}(a)^{\top} w$$



Barrier Function $h(a)$

$$\text{Log-density ratio } h(a) = \log \frac{p_+(a)}{p_-(a)}$$

Gaussian Assumption $p_{\pm}(a) = \mathcal{N}(\mu_{\pm}, I)$


$$\text{Log-density ratio } h(a) = \log \frac{p_+(a)}{p_-(a)}$$


Logistic Regression $p_{\theta}(a) = \text{sigmoid}(\theta^{\top} a)$.

$$\text{Log-density ratio } h(a) = \log \frac{p_+(a)}{p_-(a)}$$

$$= w^{\top} \phi(a) + b$$

nonlinear feature map





Thank You